
APPLICATION FOR UNITED STATES LETTERS PATENT

For

Data Management System and Method for Peripheral Devices

By

Joseph Damon Beaven
Joshua Ellingsworth
William Roger Steen

LE9-00-081

Express Mail No. EJ946017863US

DATA MANAGEMENT SYSTEM AND METHOD FOR PERIPHERAL DEVICES

BACKGROUND OF THE INVENTION

1. *Field of the Invention*

The present invention generally relates to computer systems. More particularly, the present invention relates to an operating system of managing data related to a graphic-user interface (GUI) and a peripheral device such as a printer
5 associated with a computer.

2. *Description of the Related Art*

Most operating systems of computers generate a graphic-user interface (GUI)
10 to a user that provides textual and graphical information with which a user of a computer can interact to perform various functions with the computer. Operating systems such as Windows® and the Apple Mac® O/S have a GUI that displays various virtual interactive controls, such as button, tabs, and bars that typically are interactive with the cursor of the mouse at the GUI. GUI enables a user to create,
15 modify, and respond to graphical objects in real time. A user provides a command to the computer through the GUI by utilizing a pointing or locator device, such as a mouse, trackball, joystick, or stylus with tablet. These devices convert the physical movement of the user's hand into the movement of a cursor or an object on the computer display screen, which in turn can be converted into a computer command or
20 a stream of data in digital form that can be utilized to perform various functions or predetermined actions with the computer.

To implement the GUI, the host operating system contains a GUI code directing the execution of the GUI. The host operating system also contains a data
25 management code for supervising the location, storage, and retrieval of data (including input and output to various peripherals). The data management code

manages, for example, the GUI data. Additionally, if the peripheral is a printer, the host operating system may contain a printer operating code or printer driver to operate the printer.

5 Currently, the printer operating code and the GUI code are intertwined in operating systems such as Windows® and the Apple Mac® O/S. Thus, if a modification is made to the GUI code to incorporate a new functionality, the printer operating code has to be rewritten or modified in response to the modification made to the GUI code. Likewise, if a modification is made to the printer operating code to
10 incorporate a new functionality, the GUI code has to be rewritten or modified in response to the modification made to the printer operating code. This interdependency of the printer operating code and the GUI code not only limits the applicability and flexibility of the operating system, but also increases cost and labor for modifying the codes. Additionally, bugs in the printer operating code may affect
15 the performance of the GUI code, and vice versa.

 Therefore, there exists a need for a system of managing independently data related to a graphic-user interface (GUI) and data related to a peripheral device such as a printer associated with a computer.

20

SUMMARY OF THE INVENTION

 In one aspect, the present invention is an operating system for managing data in a computer. The operating system has a main dialog module containing a graphic-
25 user interface (GUI) code for generating a GUI for interfacing between a host processor of the computer and a user. The operating system also has a data module coupled to the main dialog module, the data module containing an operating code for causing the host processor to execute a predetermined action responsive to a computer command initiated at the GUI. The operating system further has a conflict dialog
30 module coupled to the data module and having a list of conflicts, the data module causing the conflict dialog module to generate a conflict from the list of conflicts

responsive to a selected predetermined action to be executed by the host processor. In the embodiment of the present invention, the GUI code, the operating code and the list of conflicts of the conflict dialog module are independently modifiable. For example, the list of conflicts of the conflict dialog module is unaffected by a modification to the GUI code when the GUI code is modified with the modification, and vice versa. The GUI code is unaffected by a modification to the operating code, and vice versa. And the list of conflicts of the conflict dialog module is unaffected by a modification to the operating code, and vice versa. In one embodiment, the operating system of the present invention can be utilized to manage data for a peripheral device coupled to the computer.

In another aspect of the present invention, the system has a printer properties main dialog module, a printer data module and a conflict dialog module. The printer properties main dialog module contains a graphic-user interface (GUI) code for generating a GUI for displaying data for a printer in operative communication with a host processor. The printer data module is coupled to the printer properties main dialog module. The printer data module contains an operating code for operating the printer and can cause the printer to execute a predetermined action corresponding to a computer command initiated at the GUI. The conflict dialog module is coupled to the printer data module and has a list of conflicts. Each conflict is corresponding to a condition of the printer and a selected predetermined action to be executed by the printer. The printer data module causes the conflict dialog module to generate a conflict from the list of conflicts corresponding to a condition in printer setting and a selected predetermined action to be executed by the printer to alert a user of the printer. The GUI code of the printer properties main dialog module, the operating code of the printer data module and the list of conflicts of the conflict dialog module are independently modifiable.

In a further aspect, the present invention relates to a method for managing data for a printer coupled to a computer having a host processor. The method includes the steps of generating a graphic-user interface (GUI) for displaying data for a printer in

operative communication with the host processor from a GUI code, causing the printer to execute a predetermined action corresponding to a computer command initiated at the GUI from an operating code, and generating a conflict corresponding to a condition of the printer and a selected predetermined action to be executed by the printer from a list of conflicts. The method further includes the steps of modifying the list of conflicts with a modification and keeping the GUI code unaffected while the list of conflicts is modified with the modification.

The present invention further includes a computer program product in a computer readable medium of instructions. The computer program product has instructions within the computer readable medium for generating graphic-user interface (GUI) displaying data for a peripheral device in operative communication with a host processor of a computer. Additionally, the computer program product has instructions within the computer readable medium for operating the peripheral device and causing the peripheral device to execute a predetermined action corresponding to a computer command initiated at the GUI. Furthermore, the computer program product has instructions within the computer readable medium for producing a list of conflicts, each conflict corresponding to a condition of the peripheral device and a selected predetermined action to be executed by the peripheral device. The instructions within the computer readable medium for generating GUI and the instructions within the computer readable medium for producing a list of conflicts are independently modifiable. In other words, when the instructions within the computer readable medium for generating GUI are modified with a modification, the instructions within the computer readable medium for producing a list of conflicts are unaffected by the modification, and vice versa. Moreover, the instructions within the computer readable medium for operating the peripheral device and the instructions within the computer readable medium for generating GUI are independently modifiable.

The peripheral device can be a printer, a copy machine, a fax machine, a scanner, a keyboard or any combination of them. In one embodiment of the present

invention, the peripheral device is a printer, and the computer program product is an operating system for managing data in a Windows® environment of a computer with a printer coupled to the computer. The operating system can be installed in the printer controller of the printer, or in the host processor of the computer. Alternatively, the
5 operating system can be installed partially in the printer controller and partially in the host processor of the computer.

These and other aspects will become apparent from the following description of the preferred embodiment taken in conjunction with the following drawings,
10 although variations and modifications may be effected without departing from the spirit and scope of the novel concepts of the disclosure.

BRIEF DESCRIPTION OF THE DRAWINGS

15 Fig. 1 is a perspective view of a host computer in communication with a peripheral device, shown here as a printer.

Fig. 2 is a schematic block diagram of an operating system of the present invention that can be utilized in the system shown in Fig. 1.

DETAILED DESCRIPTION OF THE INVENTION

A preferred embodiment of the invention is now described in detail. Referring to the drawings, like numbers indicate like parts throughout the views. As used in the
25 description herein and throughout the claims that follow, the meaning of “a,” “an,” and “the” includes plural reference unless the context clearly dictates otherwise. Also, as used in the description herein and throughout the claims that follow, the meaning of “in” includes “in” and “on” unless the context clearly dictates otherwise.

30 With reference to Fig. 1, there is shown a perspective view of the inventive system including a host computer **8** having a host processor **12** with a display **14**, such

as a monitor, having a graphic-user interface (GUI) **20** displaying data for at least one peripheral device **10**, shown here as a printer, in operative communication with the host processor **12**. The printer **10** and host processor **12** can be in communication through any media, such as a direct wire connection **18** or through a network or the Internet **16**. Even wireless communication between the printer **10** and host processor **12** can be used with the present invention as long as data can be exchanged between the printer **10** and host processor **12**. The GUI **20** is generated by a GUI code as part of the operating system (O/S) of the host processor **12**. The printer **10** can be operated through a printer driver or operating code installed in the host processor **12** or installed in the printer **10**, in which case the printer driver communicates with the operating system of the host processor **12**.

In operation, upon receiving an input from the GUI **20**, the host processor **12** translates the input into a computer command to cause the printer **10** to execute a predetermined action responsive to the computer command. The translation may be done in one of several ways. For example, the host processor **12** could employ a look-up table resident in memory to generate a computer command. Similarly, the computer commands could be hard wired in the host processor **12** or they could be resident in firmware. The computer commands are data or instructions in digital form that are readable to the host processor **12** and the printer controller of the printer **10**. Unless the context clearly dictates otherwise, as used in the description herein and throughout the claims that follow, the meaning of “data” includes any information in digital form that is originated at, saved in, related to, or exchanged between the computer **8** and the printer **10**.

As shown in Fig. 2, an operating system **200** can be utilized to manage data for the computer **8** and the printer **10**. The system **200** includes a printer properties main dialog module **220**, a printer data module **210** and a conflict dialog module **230**. The printer properties main dialog module **220** contains a GUI code to generate the GUI **20** for displaying data for the printer **10** that is in operative communication with the host processor **12**. The printer data module **210** is coupled to the printer properties

main dialog module **220** and receives data from the printer properties main dialog module **220**. The printer data module **210** contains an operating code for operating the printer **10** and can cause the printer **10** to execute a predetermined action corresponding to a computer command initiated at the GUI **20** by a user and received from the printer properties main dialog module **220**. The conflict dialog module **230** is coupled to and owned by the printer data module **210**. The conflict dialog module **230** contains a list of conflicts. Each conflict is corresponding to a condition of the printer setting of the printer **10** and a selected predetermined action to be executed by the printer **10**. A conflict arises when a user of the printer **10** chooses a condition from the printer setting and causes the printer driver to perform a predetermined action, the intended action and the selected condition may not be compatible to each other and produce an outcome that is not desired by the user. The printer data module **210** then causes the conflict dialog module **230** to generate a conflict **232** from the list of conflicts corresponding to the condition of the printer **10** and that selected predetermined action. The conflict **232** can be displayed in the GUI **20** to alert the user of the printer **10**. For example, if a user chooses from the printer setting of the printer **10** a condition “transparency” as paper type and causes the printer driver to perform a “mirror” function, the intended “mirror” function or action and the selected condition “transparency” would produce an outcome of having a mirror image on a transparency, which may not be a desired outcome by the user. The printer data module **210** thus causes the conflict dialog module **230** to generate a conflict **232** from the list of conflicts corresponding to the condition “transparency” and the selected “mirror” function to be performed by the printer **10** to warn the user. The user has the option to correct the conflict either by selecting a new condition from the printer setting of the printer **10**, causing the printer driver to perform a new function, or both. Thus, catching a conflict and giving a user ability to correct or modify it according to the present invention enhances usability of the system.

The GUI code of the printer properties main dialog module **220**, the operating code of the printer data module **210** and the list of conflicts of the conflict dialog module **230** are not intertwined and thus independently modifiable. In other words, if

the GUI code of the printer properties main dialog module **220** is modified with a modification, for example, to incorporate a new functionality, the operating code of the printer data module **210** and the list of conflicts of the conflict dialog module **230** are unaffected by the modification. Likewise, if the list of conflicts of the conflict dialog module **230** is modified with a modification, for example, to add or incorporate a new conflict or to edit an existing conflict, the operating code of the printer data module **210** and the GUI code of the printer properties main dialog module **220** are unaffected by the modification. Similarly, if the operating code of the printer data module **210** is modified with a modification, for example, to incorporate a new functionality, the list of conflicts of the conflict dialog module **230** and the GUI code of the printer properties main dialog module **220** are unaffected by the modification.

In particular, the list of conflicts of the conflict dialog module **230** can be modified to display any functional aspect that is unique to the printer **10** even if the operating system of the host processor **12** does not recognize or interact with the full functionality of the printer **10**. Furthermore, the printer properties main dialog module **230** can translate the commands from the user at the GUI **20** into data that effects the desired changes in the peripheral device **10** independently of the host processor operating system command structure, if necessary. Moreover, the separation of the modules from intertwining to each other increases the portability of each module and thereby reduces the labor and cost for programming development.

The implementation of the printer properties main dialog module **220**, the printer data module **210** and the conflict dialog module **230** can be programmed in C++, Microsoft Visual C++ v6.0, or any other computer language that would not conflict with the operating system of the host processor **12**. The choice of C++ as the implementation language allows the developers to reuse the source code more readily than with most other languages. The operating system **200** can be operated in environment such as Windows® or the Apple Mac® O/S. Moreover, the operating system **200** can be installed in the printer **10**, or in the host processor **12**. Alternatively, the operating system **200** can be installed partially in the printer **10** and

partially in the host processor 12. For example, the printer properties main dialog module 220 may be installed in the host processor 12, and the printer data module 210 and the conflict dialog module 230 may be installed in the printer 10.

5 As those skilled in the art will appreciate, while the present invention has been described in the context of a fully functional data management system, the mechanism of the present invention is capable of being distributed in the form of a computer readable medium of instructions in a variety of forms, and the present invention applies equally regardless of the particular type of signal bearing media used to
10 actually carry out the distribution. Examples of computer readable media include: recordable type media such as floppy disks and CD-ROMs and transmission type media such as digital and analog communication links.

15 Additionally, while the present invention has been described in the context of a fully functional operating system for managing data related to a printer coupled to a computer, the mechanism of the present invention is capable of being utilized to other peripheral devices such as a copy machine, a scanner, a fax machine, a keyboard or any combination of them.

20 Indeed, the operating system of the present invention can be implemented to any Windows® applications in a Windows® environment by separating the operating code that implements the user interface from data including code related to “reactions” of the user interface to a user’s input(s), where the operating system may not be related to any peripheral devices at all. In this embodiment, the operating
25 system has a main dialog module, a data module and a conflict dialog module. The main dialog module contains a GUI code for generating a GUI for interfacing between a host processor of a computer and a user. The data module is coupled to the main dialog module and contains an operating code for causing the host processor to execute a predetermined action responsive to a computer command initiated at the
30 GUI. The conflict dialog module is coupled to the data module and has a list of conflicts, where each conflict is corresponding to a selected predetermined action to

be executed by the host processor.

While there has been shown preferred and alternate embodiments of the present invention, it is to be understood that certain changes can be made in the form and arrangement of the elements of the system and steps of the method as would be
5 known to one skilled in the art without departing from the underlying scope of the invention as is particularly set forth in the Claims. Furthermore, the embodiments described above are only intended to illustrate the principles of the present invention and are not intended to limit the claims to the disclosed elements.